

Tent image



Technical data

| | |
|----------------------------|----------------------------|
| Clear-span width | 1000 cm |
| Side height | 400 cm, 600 cm |
| Ridge height | 448 cm, 648 cm |
| Roof pitch | 5° |
| Bay distance | 500 cm |
| Gable uprights | 1 gable uprights (per end) |
| Longest component | 552 cm |
| Minimum tent length | 1000 cm |

| | |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Maximum tent length | No limit |
| Main profile | 250 mm x 120 mm x 5/4 mm |
| Eave / corner connection | Clevic-plate connection, Clevic-plate connection with corner strut |
| Max. allowed wind speed to DIN | 100 km/h |
| Wind Load | 0.5 kN/m ² |
| Extension / lean-to options | none |
| Flooring options | Woodenfloor with timber and steel sub-construction Aluminium cassettefloor with plywood or full aluminiumboards |
| Cover | RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2, inflated textile, RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2, inflated textile iso-roof |

Tent top and side view image





