

Tent image



Technical data

|                                       |  |
|---------------------------------------|--|
| <b>Clear-span width</b>               | 900 cm   |
| <b>Side height</b>                    | 229 cm   |
| <b>Ridge height</b>                   | 389 cm   |
| <b>Highest point</b>                  | 566 cm   |
| <b>Roof pitch</b>                     | 20°  |
| <b>Bay distance</b>                   | 300 cm   |
| <b>Gable uprights</b>                 | 1 gable upright (per end)  |
| <b>Longest component</b>              | 481 cm   |
| <b>Minimum tent length</b>            | As shown   |
| <b>Maximum tent length</b>            | No limit   |
| <b>Main profile</b>                   | 81 mm x 48 mm x 3 mm (optional 94 mm x 48 mm x 3 mm )  |
| <b>Eave / corner connection</b>       | Internal eave insert   |
| <b>Max. allowed wind speed to DIN</b> | 80 km/h  |
| <b>Wind Load</b>                      | 0.3 kN/m <sup>2</sup>  |
| <b>Extension / lean-to options</b>    | 1/2 hexagonal at gable end With Mega tents 6m and 8m   |
| <b>Flooring options</b>               | Woodenfloor with timber or steel sub-construction<br>Aluminium cassettefloor with plywood or full aluminiumboards Compactfloor |

**Cover**

RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2

**Note**

All Mega variations fit 6m, 8m and 9m standard party tents

Tent top and side view image

