


Tent image



Technical data

<b>Clear-span width</b>	900 cm
<b>Side height</b>	229 cm
<b>Ridge height</b>	389 cm
<b>Highest point</b>	566 cm
<b>Roof pitch</b>	20°
<b>Bay distance</b>	300 cm
<b>Gable uprights</b>	1 gable upright (per end)
<b>Longest component</b>	481 cm
<b>Minimum tent length</b>	As shown
<b>Maximum tent length</b>	No limit
<b>Main profile</b>	81 mm x 48 mm x 3 mm (optional 94 mm x 48 mm x 3 mm )
<b>Eave / corner connection</b>	Internal eave insert
<b>Max. allowed wind speed to DIN</b>	80 km/h
<b>Wind Load</b>	0.3 kN/m <sup>2</sup>
<b>Extension / lean-to options</b>	1/2 hexagonal at gable end With Mega tents 6m and 8m
<b>Flooring options</b>	Woodenfloor with timber or steel sub-construction Aluminium cassettefloor with plywood or full aluminiumboards Compactfloor

**Cover**

RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2

**Note**

All Mega variations fit 6m, 8m and 9m standard party tents

Tent top and side view image

