

Tent image



Technical data

|                                       |                                                                                                                                     |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <b>Clear-span width</b>               | 1000 cm                                                                                                                             |
| <b>Side height</b>                    | 225 cm                                                                                                                              |
| <b>Side length</b>                    | 500 cm                                                                                                                              |
| <b>Ridge height pavilion</b>          | 387 cm                                                                                                                              |
| <b>Ridge height membrane</b>          | 604 cm                                                                                                                              |
| <b>Roof pitch</b>                     | 18°                                                                                                                                 |
| <b>Longest component</b>              | 546 cm                                                                                                                              |
| <b>Main profile</b>                   | 94 mm x 46 mm x 2/4 mm                                                                                                              |
| <b>Eave / corner connection</b>       | Internal eave insert                                                                                                                |
| <b>Covered area</b>                   | 65 m <sup>2</sup>                                                                                                                   |
| <b>Max. allowed wind speed to DIN</b> | 80 km/h                                                                                                                             |
| <b>Wind Load</b>                      | 0.3 kN/m <sup>2</sup>                                                                                                               |
| <b>Extension / lean-to options</b>    | Can also be arranged as a pavilion roof with intermediate bays (see party tents Fiesta 0588/225/321, 0800/225/355 and 1000/225/387) |
| <b>Flooring options</b>               | Woodenfloor with steel sub-construction Aluminium cassettefloor with plywood or full aluminiumboards                                |

**Cover**

**Compactfloor**

RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2

**Special design**

By using compactfloor anchoring can be omitted

Tent top and side view image



